Donaldson
FILTRATION SOLUTIONS

# Product Specifications

## P771510



### AIR FILTER, PRIMARY ROUND

### Why Choose Donaldson Air Filters?

Strong, reliable gasket is compressed against the air cleaner housing to create a tight seal.

• High-efficiency cellulose media performs across a wide range of heavy-duty engine applications.

• Corrosion resistant, coated steel liners support media during operation and help maximize airflow.

• Pleatloc™ feature ensures uniform pleat spacing and prevents media from bunching to promote longer service life.

### Attributes

| | |
|---|---|
| Overall Length | 253.6 mm (9.98 inch) |
| Outer Diameter | 276 mm (10.87 inch) |
| Inner Diameter | 133.6 mm (5.26 inch) |
| Length | 242.6 mm (9.55 inch) |
| Bolt Hole Diameter | 10.5 mm (0.41 inch) |
| Efficiency | 99.9 |
| Efficiency Test Std | ISO 5011 |
| Type | Primary |

| | |
|---|---|
| Style | Round |
| Media Type | Cellulose |

## Packaged Dimensions

| | |
|---|---|
| Packaged Length | 0.343 m (13.70 inch) |
| Packaged Width | 0.343 m (13.70 inch) |
| Packaged Height | 0.263 m (10.50 inch) |
| Packaged Weight | 3.697 kg (8.15 lb) |
| Packaged Volume | 0.032 m3 (1.14 ft3) |

## Other Information

| | |
|---|---|
| NMFC Code | 069100-03 |
| UPC Code | 742330047415 |

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.